


AT-H-3.7-7.2-N



Please contact AntennaTec for a full interface control drawing.

VSWR




3.7-7.2 GHz linearly polarized horn antenna fitted with an N type connector

Key Specifications


Operating frequency band	3.7 - 7.2 GHz
Connector	N type female
VSWR	< 2:1
Gain	>18 dBi
3dB Beamwidth	25-60 degrees
Polarization	linear
Size	length 48.4cm, width 25cm
Power	200 W c.w.

This high-gain horn antenna covers the 3.7–7.2 GHz frequency range and provides focused directional performance for C-band RF applications. Its precision-engineered structure, high gain, and controlled beam characteristics make it suitable for RF testing, point-to-point communication, radar-related evaluation, monitoring systems, antenna calibration, and field measurement applications requiring stable and efficient radiation performance.


S11



Gain



Beamwidth




AntennaTec may update or improve these specifications from time to time to enhance product design, manufacturing, or performance. This document contains official AntennaTec product information and must not be reproduced, modified, or used for commercial purposes without written permission from AntennaTec.




3.7-7.2 GHz linearly polarized horn antenna fitted with an N type connector

Radiation Patterns: Red = Phi 0; Green = Phi 90


3.7GHz




4GHz




5GHz




5.5GHz



6GHz



7GHz



AntennaTec may update or improve these specifications from time to time to enhance product design, manufacturing, or performance. This document contains official AntennaTec product information and must not be reproduced, modified, or used for commercial purposes without written permission from AntennaTec.

